

Data sheet

CLENA MODEL KS/KH

Product information

- Powerful and simple build high pressure cleaner.
- Constructed in a mobile frame with large rubber Wheels.
- Automatic start/stop
- HAWK pumps with ceramic pistons.
- Easy to operate and maintain.
- Long lifetime-low costs.



Technical Specifications

MODEL	PRESSURE	FLOW	ENGINE	PART NO.
KS 160 - 15	160 bar	15 l/min	10 amp, 4 kW	30.163.015
KS 160 - 20	160 bar	20 l/min	13 amp, 5,5 kW	30.163.020
KS 200 - 15	200 bar	15 l/min	13 amp, 5,5 kW	30.203.015
KS 200 - 20	200 bar	20 l/min	16 amp, 7,5 kW	30.203.020
KS 160 - 25	160 bar	25 l/min	16 amp, 7,5 kW	30.163.025
KS 200 - 30	200 bar	30 l/min	25 amp, 11 kW	30.203.030
KS 170 - 34	170 bar	34 l/min	25 amp, 11 kW	30.173.034
KS 150 - 40	150 bar	40 l/min	25 amp, 11 kW	30.153.040
KH 160 - 15	160 bar	15 l/min	10 amp, 5,5 kW	30.260.015
KH 160 - 18	160 bar	18 l/min	13 amp, 5,5 kW	30.260.018
KH 160 - 27	160 bar	27 l/min	20 amp, 9,2 kW	30.260.027

General Specifications

- KS - Max temp. inlet.: 65 °C
- KH - Max temp. inlet.: 5 °C

Additional information

Included equipment:

- 20 meters of high-pressure hose.
- Pistol, and double lance with nozzle.
- 10 meters electric cable.

Note:

- Can be built in 3x400/440/230v and 50/60Hz
- The machines is supplied a stainless cover plate.

Data sheet

Do not hesitate to contact us if you have any special requirements.
For a machine as we can build them according to your needs.

