Data Sheet

HD Diesel Unit

Product Information

- Heavy-duty construction
- Coverplate between front to pump/motor
- HAWK pump with ceramic pistons
- · Mitsubishi 3-cyl diesel, water cooled
- 130 kW stainless boiler
- 50 m. 3/8" HP-hose, stainless steel hose reel
- 25 m. ¾" LP-hose, stainless steel hose reel
- Controlpanel in alu. with key ignition, emergency stop, thermostat, hourcounter etc.
- 80L diesel tank with level control
- Manuel gas control
- Powerfull 500 bar components
- Easy to operate and maintain
- Long ligetime low costs



Tekniske specifikationer

MODEL	PRESSURE	FLOW	ENGINE	PART NR.
UD 200 07	200 5	071/	00111	20 200 220
HD 300-27	300 bar	27 I/min	29Hk	30.300.030

Additional Information

- Dimensions: B: 1160 x L: 1270 x H:1110 mm
- Weight: 510 kg
- Hp-gun and lance is mounted
- Available with 500/15, 200/60 etc.
- Sewer Jetter available, with electric hosereel, remote control etc.
- Available in: 350-23, 500-18, 200-55

Optional equipment

- Lances
- Injector
- Surfacecleaners
- Watertank, 360/500/800/1000L

This model can be customized, let us know your requirements